



ARDEX AF 270

Linoleum and Carpet Adhesive

Dispersion-based

Solvent-free

Very low emissions

Internal use



ARDEX SINGAPORE PTE LTD
26 Tuas Ave 4 Singapore 639376
Telephone: +65 6861 7700
Fax: +65 6862 3381
Email: sales@ardex.com.sg
Website: www.ardex.com.sg

ARDEX AF 270

Linoleum and Carpet Adhesive

DESCRIPTION

Dispersion-based linoleum and carpet adhesive for absorbent subfloors indoors.

USE

For the laying of

- linoleum floorings
- corkment coverings
- tufting floorings with matted backing, synthetic second backing or jute backing
- woven floorings
- needle fleece floorings

SUBFLOOR PREPARATION

Subfloors must be level, permanently dry, solid and free from cracks, dirt and adhesion-inhibiting substances. Apply corresponding ARDEX levelling compounds to non-absorbent and uneven subfloors

APPLICATION

Stir adhesive well before using. Using a notched trowel, apply uniformly on the subfloor, avoiding adhesive pools.

Insert flooring and press down well. Rub again as soon as adhesive clearly begins to hold. Weigh down extremely annoying edges of flooring covering if necessary for setting the adhesive. Grout seams in the linoleum only after an adhesive setting time of 48 hours.

NOTE: Processing not below floor temperature of +15°C and room temperature of +18°C, as well as room humidity preferably between 40% and 65%, maximum 75%. In cold weather, warm up ARDEX AF 270 in due time in heated room.

TECHNICAL DATA

Raw material base:	Acrylate dispersion
Airing time:	approx. 0 - 10 minutes
Working time:	approx. 15 minutes
Coverage:	approx. 325 - 450 g/m ²
Cleaning agent:	Water, before the adhesive starts to dry
Storage time:	12 months at room temperature

PACKAGING

ARDEX AF 270 is packed in a 14 kg plastic pail.

STORAGE

ARDEX AF 270 should not be stored in direct contact with sun and protected from freezing. When stored under the correct conditions and unopened, it has a shelf life of 12 months.

SAFETY PRECAUTIONS

Keep out of reach of children Irritant: Avoid eye and skin contact. Use only in well ventilated areas. Keep container tightly closed. In case of contact with eyes and skin, rinse with plenty of water. In event of irritation, seek for medical advice according to the Material Safety Datasheet.

DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at the time of printing. They are primarily offered for user's consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products. It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the product instructions and recommendations and only for the uses they are intended. As we have no control over site conditions and the execution of the work, we accept no liability for any loss or damage which may rise as a result thereof.. also reserve the right to update the information at any time without tice to to without prior notice to you to reflect our ongoing research and development program.

Offices:

Malaysia:

ARDEX MANUFACTURING SDN BHD (669180-X)
No. 19-1, Jalan Puteri 2/2, Bandur Puteri,
47100, Puchong, Selangor Darul Ehsan
Tel: +60 38060 1139 Fax: +60 38060 0719
Email: sales@ardex.com.sg

Thailand:

ARDEX (THAILAND) CO., LTD
969 2nd Floor Moo, 13, Soi 45, Bangna-Trad Road
Bangkaew, Bangplee, Samutprakarn 10540 Thailand
Tel: +66 2316 3069 Fax: +66 2316 3075
Email: sales@ardex.co.th

Vietnam:

Mobile: +84 901 351 308
Email: sales@ardex.com.sg

September 2016